

Operating Systems

Grado en Informática. Course 2025-2026

Lab assignment 0: Introduction to the C programming language

To get acquainted with the C programming language we'll start to code a shell, coding of this shell will be continued in next lab assignments. In this shell we have to keep two lists: one for the commands input to the shell, and other of the shell's opened files

We'll start with a nearly empty shell, which is basically a loop that

- prints a *prompt*
- reads from the standard input a line of text which includes a command (with its arguments).
- stores this command in a list of commands that it has been given, each with its order number in a list we'll call the *historic* of commands.
- separates the command and its arguments
- processes the comand with its arguments

At this moment this *shell* has to understand only the commands described below. In the next lab assignments we will be **COMPLETING** this shell: we **BUILD lab assignment 1 ON the code of lab assignment 0**, lab assignment 2 ON the code of lab assignment 1 and so on

This shell must also have the ability of opening and closing files with the *open* and *close* system calls (**DO NOT USE THE `fopen()` and `fclose()` library functions**). It can also duplicate file descriptors (with the *dup* system call). The shell must keep a list of its open files (simply enough: it adds an item to this list each time it successfully opens a file with the command *open* and removes an entry each time it closes a file (successfully) with the command *close*). We can examine with the appropriate command (*openor listopen*), and it must be coherent with the list the system has (available with `ls -l /proc/shell_pid/fd` in linux, or `procstat -f shell_pid` in FreeBSD).

The provided file `ayudaP0.c` provides some code that can be used for this lab assignment.

authors Prints the names and logins of the program authors. **authors -l** prints only the logins and **authors -n** prints only the names

getpid Prints the pid of the process executing the shell.

getpid -p Prints the pid of the shell's parent process.

chdir [**dir**] Changes the current working directory of the shell to *dir* (using the *chdir* system call). When invoked without arguments it prints the current working directory (using the *getcwd* system call).

getcwd Prints the current working directory of the shell (using the *getcwd* system call).

date [**-t**|-**d**] Prints the current date in the format DD/MM/YYYY and the current time in the format hh:mm:ss.

date -d Prints the current date in the format DD/MM/YYYY

date -t Prints and the current time in the format hh:mm:ss.

hour Prints and the current time in the format hh:mm:ss. (*same as date -t*)

historic [**N**|-**N**] Shows the *historic* of commands executed by this shell. In order to do this, a list to store all the commands input to the shell must be implemented.

- **historic** Prints all the comands that have been input with their order number

- **historic N** Repeats command number N (from historic list)

- **historic -N** Prints only **the last** *N* comands

historic [**-clear**|-**count**] Clear the historic list or report its number of elements

- **historic -count** Reports how many commands there are on the historic list

- **historic -clear** Clears the historic list

Students are free to decide whether *historic* starts numbering commands at 0 or at 1. Hypothetically, there's a scenario where trying to repeat a *historic* command could yield an infinite loop or a stack overflow (depending on how it is coded), so students may choose to not store calls to *historic N* itself in the historic list if they want so (See the *NOTES ON LIST IMPLEMENTATIONS* at the end of this document)

open [**file**] **mode** Opens a file and adds it (together with the file descriptor and the opening mode to the list of shell open files. For the mode we'll use **cr** for O_CREAT, **ap** for O_APPEND, **ex** for O_EXCL, **ro** for O_RDONLY, **rw** for O_RDWR, **wo** for O_WRONLY and **tr** for O_TRUNC.

Open without arguments lists the shell open files. For each file it lists its descriptor, the file name and the opening mode. The shell will inherit from its parent process its open descriptors -usually 0, 1 and 2 (stdin, stout, and stderr). To get the opening mode from a descriptor (*df*) we can use *fcntl(df,F_GETFL)*.

close [**df**] Closes the *df* file descriptor and eliminates the corresponding item from the list

- dup [df]** Duplicates the *df* file descriptor (using the *dup* system call, creating the corresponding new entry on the file list)
- listopen** Lists the shell open files, This is the same as the *open* command without arguments
- infosys** Prints information on the machine running the shell (as obtained via the *uname* system call/library function)
- help [cmd]** *help* displays a list of available commands. *help cmd* gives a brief help on the usage of comand *cmd*
- quit** Ends the shell
- exit** Ends the shell
- bye** Ends the shell

IMPORTANT

- This program should compile cleanly (produce no warnings even when compiling with `gcc -Wall`)
- **NO RUNTIME ERROR WILL BE ALLOWED** (**segmentation, bus error ...**), unless where explicitly spcified. **Programs with runtime errors will yield no score.**
- This program can have no memory leaks (please use `valgrind` to check)
- When the program cannot perform its task (for whatever reason, for example, trying to change the current working directory to a directory that does not exist or that shell has not enough privileges), it should inform the user, giving an appropriate description of the error such as the one given by `strerror()`, `perror()`, `sys_errlist[errno]` ...
- All input and output in the shell must be done through the standard input and the standard output. We can use **EITHER** the `(read(0, ,)` and `write(1, ,)` pair **OR** the `fgets` and `printf` pair. Mixing `read` and `write` with `fgets` and `printf` for the shell's input/output is strongly discouraged
- Executable files of an implementation of this shell are provided. Please check out them for any doubts.
- Students must use **ONE OF THE LIST IMPLEMENTATIONS** commented below.

Information on the system calls and library functions needed to code this program is available through man: (*printf*, *fgets*, *read*, *write*, *exit*, *getpid*, *getppid*, *getcwd*, *chdir*, *time*, *open*, *close*, *dup* ...).

CLUES

A shell is basically a loop

```
while (!terminado){
    imprimirPrompt();
    leerEntrada();
    procesarEntrada();
}
```

imprimirPrompt() and *leerEntrada()* can be as simple as calls to **printf** y **gets** (there's a reason why *fgets()* should be used instead of *gets()*)

The first step when processing the input string is splitting it into words. For this, the **strtok** library function comes in handy. Please notice that **strtok** does not allocate memory neither does it copy strings, it just breaks the input string by inserting end of string ('\0') characters. The following function splits the string pointed by *cadena* (suposedly not null) into a NULL terminated array of pointers (*trozos*). The function returns the number of words that were in *cadena*

```
int TrocearCadena(char * cadena, char * trozos[])
{ int i=1;

    if ((trozos[0]=strtok(cadena," \n\t"))==NULL)
        return 0;
    while ((trozos[i]=strtok(NULL," \n\t"))!=NULL)
        i++;
    return i;
}
```

NOTES ON LIST IMPLEMENTATION

- the implementations of list should consist of the data types and the access funtions. All access to the list should be done used the aforementioned access functions.
- students can choose from one of these three list implementations
 - 0) **linked list**: The list is composed of dynamically allocated nodes. Each node has some item of information and a pointer to the following node. The list itself is a pointer to the first node, when the list is empty this pointer is NULL, so creating the list is asigning NULL to the list pointer, thus the functions **CreateList**, **InsertElement** and **RemoveElement** must receive the list by reference as they may have (case of inserting or removing the first element) to modify the list. There can also be used a double linked

version of this list (each node has two pointers)

- 1) **linked list with head node:** Similar to the linked list except that the list itself is a pointer to an *empty* (with no information) first node. Creating the list is allocating this first element (head node). `CreateList` must receive the list by reference whereas `InsertElement` and `RemoveElement` can receive the list by value. There can also be used a double linked version of this list (each node has two pointers)
- 2) **array of pointers;** The list is an array (either statically or dynamically allocated) of pointers. Each pointer points to one element in the list which is allocated dynamically. For the purpose of this lab assignment we can assume, should we want so, this statically allocated array dimension to be 4096, which should be declared a named constant, and thus easily modifiable. To implement the list with this array we can use either a NULL terminated array or we can use additional integers. We could also make the list completely dynamic by using a dynamically allocated pointer instead the fixed size array of pointers

WORK SUBMISSION

- Work must be done in pairs.
- All code must be in a folder named P0 (capital P). A zip file (p0.zip) containing that very directory (together with its files) is what is going to be submitted
- The name of the main program file will be `p0.c` in a folder named P0. Program must be able to be compiled with `gcc p0.c` Alternatively a `Makefile` can be supplied in the folder P0 so that the program can be compiled with just `make`. The final executable will be named *a.out*
- Only one of the members of the workgroup will submit the source code. **The names and logins of all the members of the group should be in the source code of the main program** (at the top of the file, as comments)
- DEADLINE: September, Friday the 26th. This lab assignment will **yield no score, neither will it be evaluated**. However all the code for this assignment **must be reutilized** for the following assignments. This assignment will also help get acquainted with the submission procedure of all of the following lab assignments (**from the next assignment on, work wrongly submitted will no be evaluated**)
- Submission procedure will be announced at a later date